



NOTES:

1. SOLVENT WELD ALL JOINTS (NON GASKETED).
2. IN ALL CASES, INSTALL A 6' HEAVY METAL TEE POSTS TO 3' ABOVE FINISHED GRADE AND PAINT TOP 6" OF POST FLUORESCENT GREEN. OVERLAP METAL TEE POST 1' WITH 2"x2" WOOD MARKER POST.
3. ANY REQUIRED CLEANOUTS SHALL NOT BE LOCATED WITHIN THE PUBLIC RIGHT-OF-WAY.
4. ALL PIPE SHALL BE BEDDED ON GRANULAR BEDDING (MNDOT 3149.2-F) OR COURSE FILTER AGGREGATE (MNDOT 3149.2-H).
5. INSTALL TRACER WIRE SYSTEM PER SPEC'S AND DETAIL PLATE 5507.
6. WHEN A SIDEWALK OR TRAIL IS PRESENT IN THE BLVD. THE SERVICE MAY BE EXTENDED INTO THE D&U EASEMENT WITH THE CITY ENGINEERS APPROVAL.



TYPICAL SANITARY SEWER SERVICE (LESS THAN 16' DEEP)

REVISED: 2-24

ENGINEERING DEPARTMENT

PLATE NO.:

2001