



NOTES:

- 1. SHOULDERS TO BE BACKFILLED AND RESTORED WITH TOPSOIL AND RE-VEGETATED WITH SOD OR SEED / MULCH.
- 2. THE CONTRACTOR OR DEVELOPER SHALL SUPPLY A 2 YEAR 100% MAINTENANCE BOND UPON CITY ACCEPTANCE.
- 3. THIS DETAIL / SPECIFICATIONS ARE MINIMUMN REQUIREMENTS, ADDITIONAL DESIGN MAY BE REQUIRED DEPENDING ON EXISTING SUB-GRADE SOIL CONDITIONS.
- 4. BITUMINOUS TRAILS MAY NOT BE CONSTRUCTED ON UNSUITABLE SOILS. NO WASTE MATERIAL, BLACK DIRT, OR ORGANIC SOILS ALLOWED.
- 5. PATCHING OF EXISTING TRAILS SHALL BE FULL WIDTH AND NO LESS THAN 4' LONGITUDINALLY .
- 6. A 20' RADIUS SHALL BE USED WHEN TRAILS INTERSECT TRAILS.
- 7. NO RADIUS REQUIRED WHEN TRAILS INTERSECT SIDEWALKS.



BITUMINOUS TRAIL

REVISED: 3-23

FILE NAME: G: \ENG\SPECS\5216

ENGINEERING DEPARTMENT

PLATE NO.:

5216